



NIPPON KAIJI KYOKAI

TYPE APPROVAL CERTIFICATE FOR AUTOMATIC DEVICES AND EQUIPMENT

Certificate No. TA14522M

This is to certify that the undernoted product(s) has/have been approved in accordance with the requirements specified in Chapter 1, Part 7 of "Guidance for the Approval and Type Approval of Materials and Equipment for Marine Use" and the relevant Society's Rules.

This certificate is issued to

Manufacturer:

Danfoss Sp. z o. o.

Place of Manufacturing:

UI. Chrzanowska 5, Grodzisk, Mazowiecki, POLAND

Product description:

Differential Pressure Controls

Model:

CAS155

Approval No.:

84A157

Valid until:

8 July 2019

This certificate is subject to the conditions specified in the attached sheet(s).

Issued at Tokyo on 9 July 2014.

Y. Shibata

General Manager

Machinery Department

Note: The manufacturer, if desired, is requested to apply to the Society for renewal prior to the expiration date.

NIPPON KAIJI KYOKAI

Attached sheet -1/2 to the Certificate No. TA14522M

Specification & documents:

1. Particulars:

Pressure Range:

0.02 - 0.25 MPa

Contact Load:

AC 250V 0.1A

DC 125V 12W

2. Components and reference drawings:

Component	Model	Drawings
Differential Pressure Controls	CAS155	060R0251, 060R0252, 060R0253, 060R0254, 027M0024-1/2, 2/2

3. Documentation and Test Reports:

Type approval tests report (1) (Danfoss, TR 60-763, 1984-3-23)

Type approval tests report (2) (Danfoss, CG-LF/OJN/hh, 1994-4-19)

NIPPON KAIJI KYOKAI

Attached sheet -2/2 to the Certificate No. TA14522M

Test items & approval conditions:

1. Test items:

(Applied testing items are marked with X.)

ENVIRONMENTAL TESTS .		Mark
External examination		X
Operation test and performance test		X
Electric power supply failure test		
Dayyan ayanlış flyatyatian taat	Electric	
Power supply fluctuation test	Pneumatic and Hydraulic	
Insulation resistance test		X
High voltage test		
Pressure test		X
Dry heat test (Temperature 70°C×48 hou	eat test (Temperature 70°C×48 hours)	
Damp heat test (Temperature 55°C, Humidity 90%×16 hours×4 cycles)		X
Vibration test (Acceleration $\pm 4.0 \text{g} \times 2 \text{ hours}$)		X
Inclination test		
Cold test (Temperature $-25^{\circ}\text{C} \times 19 \text{ hours}, -50^{\circ}\text{C} \times 2 \text{ hours}$)		X
Salt mist test		
Electrostatic discharge immunity test		
Radiated radio frequency immunity test		
Conducted low frequency immunity test		
Conducted high frequency immunity test		
Burst / Fast transient immunity test		
Surge immunity test		
Radiated emission test		
Conducted emission test		
Flame retardant test		